

SI-200A

Ex ia Fixed Gas Detector



DESCRIPTION

SI-200A is an intrinsically safe (Ex ia) fixed gas detector designed to provide fast and accurate detection of toxic gases such as HCl, NH<sub>3</sub>, and Cl<sub>2</sub>—gases that typically experience delayed response due to adsorption in conventional flameproof (Ex d) detectors. With an optimized sensor housing and internal structure, SI-200A minimizes adsorption effects and ensures superior response time and measurement accuracy.

This diffusion-type explosion-proof detector is suitable for hazardous areas where toxic, oxygen, or combustible gases may be present. It features a large LCD for real-time gas concentration and self-diagnostics. The device supports 4–20mA analog output (HART optional), RS-485 digital communication, and offers convenient wireless configuration and calibration via wireless.

KEY FEATURES

- Explosion-proof structure (Transmitter)
- Intrinsically safe sensor housing
- Optimized for fast and accurate detection of adsorptive toxic gases (e.g., HCl, NH<sub>3</sub>, Cl<sub>2</sub>)
- 4-digit gas concentration display
- Self-diagnostic function via LCD
- 4–20mA output (HART optional) / RS-485 communication
- Wireless communication supported
- Suitable for hazardous area installation

SPECIFICATION

Model	SI-200A	
Dimensions	169mm (W) x 188.5mm (D) x 107mm (H)	
Weight	2.4kg	
Operation Power	DC : +24Vdc ±10%	
Power Consumption	3.6W @+24VDC	
Operation Mode Display	FND, Concentration of Gas, Alarm, Malfunction	
Relay	1st Alarm, 2nd Alarm, Fault Alarm (Rated 2.0A @30vdc)	
Analog Output Signal	4-20mA	
Digital Output Signal	RS-485	
Measuring Method	Diffusion	
Operating Temperature	-40°C to +60°C	
IP	IP66	
Input and Setting	4 Buttons & RS-485 & Bluetooth	
Device Warranty	2 years	
Sensor Warranty	1 year	
Wireless interface	RS-485 Modbus, HART (Option)	
Certification	KCs	Ex db ia IIC T4 Gb
	IECEX	Ex ia IIC T4 Gb

